

KABL-P4

Oljebeständig och flexibel
PUR-kabel. 4 x 0,33 mm².
Ytterdiameter Ø 5 mm, 80°C



<i>SPECIFICATION</i>		
CONDUCTORS	MATERIAL	BARE COPPER
	AWG	#22
	CONSTRUCTION	0.1/42
	LAY(mm)	15 Max.
INSULATION	MATERIAL	SR PVC-35P
	O.D.	1.3±0.05mm
	COLOR	WHITE,BLUEB, BLACK,ROWN
CABLING	WIRE NO.	4C
	LAY(mm)	40±5
JACKET	MATERIAL	PU 85A
	FINAL O.D.	5.00 +0/-0.15
	COLOR	SEMI GLOSSY BLACK (AS SAMPLE)
MARKING	POLYURETHANE JACKET 4C/22AWG 80°C 300V	
	FONT : Arial	PITCH : 320 mm
	COLOR : WHITE	HEIGHT : 1.2 mm
FLEXIBLE TEST	LOADING	500g
	RADIUS	5m/m
	ANGLES	±90°
	FREQ.	100 Times/Minute
	REQUIREMENT	5000 Times
Others	STRIPPING	Must be easy at 50mm(MAX.) length
	INSULATION RESISTANCE	10M ohm (MIN.)

HM 2103

