


Temperature switches with fixed set-point and 360° rotating head



Switch rating	10 A / 240 Vac 05 A / 24 Vdc 10 A / 12 Vdc
Max. pressure	200 bar
Max. differential DT	16°C
Accuracy	±5°C
Environment temperature	-20°C to +120°C
Protection	IP65
Connector	DIN 43650 form A PG09 or PG11
Body material 27 AF	Natural anodized aluminium
Body material	Thermoplastic
Tightening torque	30 Nm
Weight	70 g

<table border="1"> <tr> <td>Model</td> <td>NTB</td> </tr> </table>		Model	NTB	<table border="1"> <tr> <td>HM-NTB</td> <td>90</td> <td>C</td> <td>C</td> </tr> </table>	HM-NTB	90	C	C	<table border="1"> <tr> <td>Contact</td> <td>A - C</td> </tr> </table>	Contact	A - C					
Model	NTB															
HM-NTB	90	C	C													
Contact	A - C															
<table border="1"> <tr> <td>Operating temperature°C</td> <td>25 - 31 - 38 - 47 - 60 - 70 - 80 - 90 - 100 - 105</td> </tr> </table>		Operating temperature°C	25 - 31 - 38 - 47 - 60 - 70 - 80 - 90 - 100 - 105	<table border="1"> <tr> <th>"C"</th> <th>Thread</th> <th>"B"</th> </tr> <tr> <td>B</td> <td>G 3/8" cilindrica / Parallel</td> <td>14</td> </tr> <tr> <td>C</td> <td>G 1/2" cilindrica / Parallel</td> <td>14</td> </tr> <tr> <td>D</td> <td>M22x1.5 cilindrica / Parallel</td> <td>14</td> </tr> </table>	"C"	Thread	"B"	B	G 3/8" cilindrica / Parallel	14	C	G 1/2" cilindrica / Parallel	14	D	M22x1.5 cilindrica / Parallel	14
Operating temperature°C	25 - 31 - 38 - 47 - 60 - 70 - 80 - 90 - 100 - 105															
"C"	Thread	"B"														
B	G 3/8" cilindrica / Parallel	14														
C	G 1/2" cilindrica / Parallel	14														
D	M22x1.5 cilindrica / Parallel	14														

HM-NTB	<i>Temperature switches with fixed set-point</i>
<i>Operating temperature</i>	25°C
	31°C
	38°C
	47°C
	60°C
	70°C
	80°C
	90°C
	100°C
	105°C
<i>Available threads "C"</i>	B G 3/8" parallel
	C G 1/2" parallel
	D M22x1.5 parallel
<i>Contact type</i>	A NO normally open
	C NC normally closed