



Online Data sheet

HM 2602

Encoder WDGA 58E RS485

www.wachendorff-automation.com/wdga58ers485

Wachendorff Automation

... systems and encoders

- Complete systems
- Industrial rugged encoders to suit your application
- Standard range and customer versions
- Maximum permissible loads
- 48-hour express production
- Made in Germany
- Worldwide distributor network



Nyckelvägen 7
142 50 SKOGÅS, Sweden

Tel: +46 (0)8 771 02 20
info@hemomatik.se

www.hemomatik.se

IndustrieROBUST

Encoder WDGA 58E absolute RS485, with EnDra® Technology



Illustration similar

EnDra®
Technologie

RS485

- EnDra® multiturn technology: maintenance-free and environmentally friendly
- RS485
- Single-turn/Multi-turn (max. 16 bit /32 bit)
- Forward-looking technology with 32 bit processor
- CRC checksum

www.wachendorff-automation.com/wdga58ers485

Mechanical Data

| | |
|--------------------------------|---|
| Flange | hollow shaft (blind-bored) |
| Flange material | aluminum |
| Housing material | Aluminum die cast, powder coated; Integrated magnetic shielding |
| Torque supports | incl. 1 torque support WDGDS10001 |
| - 1. Spring plate compensation | axial: ±0.8 mm [0.0315"], radial: ±0.2 mm [0.0079"] |
| - Max. operating speed | 6000 rpm up to max. protection rating +60 °C |
| - 2. Cylinder pin 4 mm | needs accessories WDGDS10005 |
| - Compensation | axial: ±0.5 mm [0.0197"], radial: ±1.5 mm [0.0591"], Max. operating speed: 3000 rpm |
| Flange diameter | Ø 58 mm [Ø 2.283"] |

Shaft(s)

| | |
|---------------------------------------|---|
| Shaft material | stainless steel |
| Starting torque | approx. 1.6 Ncm [2.266 in-ozf] at ambient temperature |
| Fixing | permanently attached clamping ring |
| Shaft | Ø 6 mm [Ø 0.236"] |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 6.35 mm [Ø 1/4"] Order No: 2Z |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 7 mm [Ø 0.276"] |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |

| | |
|---------------------------------------|----------------------------------|
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 8 mm [Ø 0.315"] |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 9.525 mm [Ø 3/8"] Order No: 4Z |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 10 mm [Ø 0.394"] |
| Advice | with adapter sleeve |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 12 mm [Ø 0.472"] |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 14 mm [Ø 0.551"] |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |

| | |
|---------------------------------------|--------------------|
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |
| Shaft | Ø 15 mm [Ø 0.591"] |
| Shaft length | L: 12 mm [0.472"] |
| Insertion depth min. | 11 mm [0.433"] |
| Insertion depth max. | 15 mm [0.591"] |
| Max. Permissible shaft loading radial | 80 N [8.157 kp] |
| Max. Permissible shaft loading axial | 50 N [5.098 kp] |

Bearings

| | |
|----------------------|---|
| Bearings type | 2 precision ball bearings |
| Nominal service life | 1 x 10 ⁹ revs. at 100 % rated shaft load 1 x 10 ¹⁰ revs. at 40 % rated shaft load 1 x 10 ¹¹ revs. at 20 % rated shaft load |
| Max. operating speed | 6000 rpm |

Machinery Directive: basic data safety integrity level

| | |
|-----------------------------|--|
| MTTF _d | 1000 a |
| Mission time (TM) | 20 a |
| Nominal service life (L10h) | 1 x 10 ¹¹ revs. at 20 % rated shaft load and 6000 rpm |
| Diagnostic coverage (DC) | 0 % |

Electrical Data

| | |
|----------------------------------|------------------------------------|
| Power supply/Current consumption | 4,75 VDC up to 32 VDC: typ. 50 mA |
| Power consumption | max. 0.5 W |
| Power supply/Current consumption | 4,75 VDC up to 5,5 VDC: typ. 80 mA |
| Power consumption | max. 0.44 W |
| Operating principle | magnetic |

Sensor data

| | |
|-----------------------------|--|
| Single-turn technology | innovative hall sensor technology |
| Single-turn resolution | up to 65,536 steps/360° (16 bit) |
| Single-turn accuracy | ± 0.0878° (12 bit) |
| Single-turn repeat accuracy | ± 0.0878° (12 bit) |
| Internal cycle time | 600 µs |
| Multi-turn technology | patented EnDra® technology no battery no gear. |
| Multi-turn resolution | up to 32 bit. |

Environmental data

| | |
|----------------------------------|--|
| ESD (DIN EN 61000-4-2): | 8 kV |
| Burst (DIN EN 61000-4-4): | 2 kV |
| includes EMC: | DIN EN 61000-6-2 DIN EN 61000-6-3 DIN EN 61326-1 |
| Vibration: (DIN EN 60068-2-6) | 300 m/s ² (10 Hz up to 2000 Hz) |
| Shock: (DIN EN 60068-2-27) | 5000 m/s ² (6 ms) |
| Electrical Safety: | according DIN VDE 0160 |
| Turn on time: | <1,5 s |

Duty information

| | |
|------------------------|----------|
| Customs tariff number: | 90318020 |
|------------------------|----------|

| | |
|--------------------|---------|
| Country of origin: | Germany |
|--------------------|---------|

Interface

| | |
|------------|--------------|
| Interface: | RS485 |
|------------|--------------|

Configuration inputs:

| | |
|--|---|
| Positive direction of counting: (View on shaft) | DIR = GND -> cw DIR = +Ub -> ccw |
| Set to zero: | Preset = apply +Ub for 2 s |
| Baud rate: | Standard: 9600 bit/s Other baud rates on request |
| Polling cycle: | Standard: 20 ms (Tolerances: +/- 2 ms) Other polling cycles on request |

| | |
|------------------|-------------------------------------|
| Telegram length: | 6 byte singleturn, 8 byte multiturn |
|------------------|-------------------------------------|


| | |
|-----------------------|---|
| Telegram composition: | 2 Byte Präambel, 2 / 4 Byte user data, 2 Byte CRC |
|-----------------------|---|

| | |
|------------------|--|
| Bytecomposition: | Startbit (0) and Stopbit (1), Bytes are Big-Endian and LSB first, no Paritybit |
|------------------|--|

| | |
|-----------------|---|
| CRC-Definition: | Code: <ul style="list-style-type: none"> • CRC-CCITT 16 bit (X¹⁶+X¹²+X⁵+1) • Startvalue 0x1021, • Start/Stopbits aren't included • Präambel (0xABCD) is included, • Byte-wise orientation: per CRC-Refresh there is used 1 Byte |
|-----------------|---|

| | |
|---------------------------------|--|
| Protocol malfunction behaviour: | If encoder recognizes that it's impossible to send a right positionvalue (e.G.: Magnet-loss), there will be send out a telegram with maximum value user Data at normalcycletime and normal Baudrate. |
|---------------------------------|--|

Protocol RS485




General Data

| | |
|------------------------------|--|
| Weight | approx. 220 g [7.76 oz] |
| Connections | cable or connector, radial |
| Protection rating (EN 60529) | Housing: IP65, IP67; shaft sealed: IP65; cable outlet K1: IP40 |
| Operating temperature | -40 °C up to +85 °C [-40 °F up to 185 °F] |
| Storage temperature | -40 °C up to +100 °C [-40 °F up to 212 °F] |

More Information

| | |
|--|---|
| General technical data and safety instructions | http://www.wachendorff-automation.com/gtd |
| Options | http://www.wachendorff-automation.com/acc |

Cable connection L3 radial with 2 m cable




Description

L3 radial, shield connected to encoder housing

| Assignments | |
|------------------|-----------|
| | L3 |
| S- (GND) | WH |
| S+ (DCin) | BN |
| A (DATA+) | GY |
| B (DATA-) | PK |
| PRESET | BU |
| DIR | RD |
| Shield | housing |

Connector, M12x1, CC8, radial, 8-pin




Description

CC8 radial, 8-pin, shield connected to encoder housing

| Assignments | |
|------------------|----------------|
| | CC8 |
| S- (GND) | 1 |
| S+ (DCin) | 2 |
| A (DATA+) | 5 |
| B (DATA-) | 6 |
| PRESET | 7 |
| DIR | 8 |
| Shield | housing |

Connector, M23, C5, radial, 12-pin



Description

C5 radial, 12-pin, shield connected to encoder housing

| Assignments | |
|------------------|------------------|
| | <p>C5</p> |
| S- (GND) | 12 |
| S+ (DCin) | 11 |
| A (DATA+) | 3 |
| B (DATA-) | 4 |
| PRESET | 9 |
| DIR | 8 |
| Shield | housing |

Options

Low-friction bearings

The encoder WDGA 58E RS485 is also available as a particularly smooth-running low-friction encoder. The starting torque is thereby changed to approx. 0.6 Ncm [0.85 in-ozf] at ambient temperature and the protection class at the shaft input to IP50.

Order key

AAC

| Example Order No. | Type | Your encoder |
|-------------------|---|------------------|
| WDGA 58E | WDGA 58E | WDGA 58E |
| | Shaft | Order key |
| 06 | Ø 6 mm [Ø 0.236"] with adapter sleeve | 06 |
| | Ø 6.35 mm [Ø 1/4"] Order No: 2Z with adapter sleeve | 2Z |
| | Ø 7 mm [Ø 0.276"] with adapter sleeve | 07 |
| | Ø 8 mm [Ø 0.315"] with adapter sleeve | 08 |
| | Ø 9.525 mm [Ø 3/8"] Order No: 4Z with adapter sleeve | 4Z |
| | Ø 10 mm [Ø 0.394"] with adapter sleeve | 10 |
| | Ø 12 mm [Ø 0.472"] | 12 |
| | Ø 14 mm [Ø 0.551"] | 14 |
| | Ø 15 mm [Ø 0.591"] | 15 |
| | Single-turn Resolution | Order key |
| 14 | Single-turn resolution 1 bit up to 16 bit, recommended min. 6 bit (e. G. 14 bit) | 14 |
| | Multi-turn Resolution | Order key |
| 18 | Multi-turn up to 32 bit (e. G. 18 bit) (Single-turn + Multi-turn max. 32 bit) No Multi-turn: 00 | 18 |
| | Data protocol | Order key |
| EI | RS485 | EI |
| | Software | Order key |
| A | up to date release | A |
| | Code | Order key |
| B | binary | B |
| | Power supply | Order key |
| 0 | 4.75 V up to 32 V (standard) | 0 |
| | 4.75 V up to 5.5 V | 1 |
| | Galvanic isolation | Order key |
| 0 | no | 0 |
| | Electrical connections | Order key |
| CC8 | Cable: radial, shield connected to encoder housing, with 2 m cable | L3 |
| | Connector: sensor-connector, M12x1, 8-pin, radial, shield connected to encoder housing | CC8 |
| | connector, M23, 12-pin, radial, shield connected to encoder housing | C5 |
| | Options | Order key |
| | Without option | Empty |
| | Low-friction bearings | AAC |

| | | | | | | | | | | | |
|--------------------------|----------|----|----|----|----|---|---|---|---|-----|--|
| Example Order No. | WDGA 58E | 06 | 14 | 18 | EI | A | B | 0 | 0 | CC8 | |
|--------------------------|----------|----|----|----|----|---|---|---|---|-----|--|

| | | | | | | | | | | | |
|----------|--|--|--|--|--|--|--|--|--|--|--------------------------|
| WDGA 58E | | | | | | | | | | | Example Order No. |
|----------|--|--|--|--|--|--|--|--|--|--|--------------------------|