

UR-DS Series

FASTUS IO-Link hub

UR-DS16D

UR-DS8D8T

UR-DS16T

HM 2505

Item			Specifications		
Unit			IO-Link Digital I/O hub		
Model code			UR-DS16D	UR-DS8D8T	UR-DS16T
Interface	Number of points		1 (Use either spring clamp terminal blocks or e-CON socket)		
	IO-Link	Version	1.1		
		Master/Device	Operates as device		
		Communication speed	COM3 (230.4 kbps)		
		Process input data	2 bytes	2 bytes	2 bytes
		Process output data	1 byte	3 bytes	4 bytes
		Minimum cycle time	0.4 ms	0.6 ms	0.5 ms
		Cable length	Maximum 20 m		
I/O terminal	Number of points		16 (spring clamp terminal block)*UR-DE: e-CON socket		
	Digital input	Points	16	8	-
		Type of input	Source, PNP or Sink, NPN (selectable for all channel)		-
		Dielectric withstanding voltage	500 VAC for one minute between I/O terminal batch and IO-Link batch		-
		Insulation resistance	10 M ohm or higher between I/O terminal batch and IO-Link batch		-
		Common	Shared with 16 channels	Shared with 8 channels	-
		Rated input voltage	24 VDC including ripple (P-P) 5 %		-
		Rated input current (typical values)	4.9 mA		-
		Insulation method	Photocoupler insulation		-
		Maximum number of Simultaneous input points	100 % simultaneous ON		-
		Voltage and current at ON	15 V or higher, 3 mA or higher		-
		Voltage and current at OFF	8 V or less, 1.5 mA or less		-
		Input resistance	4.7 k ohm		-
		Input response time	0 to 200 ms (1 ms unit, default value of 10 ms)		-

OPTEX FA CO., LTD.

78046-00-001-2304

page1/2

Item			Specifications		
Model code			UR-DS16D	UR-DS8D8T	UR-DS16T
I/O terminal	Digital output	Points	-	8	16
		Type of output	-	Source, PNP or Sink, NPN (selectable per channel)	
		High current output function	-	Channel C to F for Source, PNP, output	
		Rated load voltage	-	12/24 VDC (allowable voltage from 10.2 to 28.8 VDC)	
		Maximum load current	-	Standard output: 0.5 A per point High current output: 4 A per point	
		Maximum total load current	-	12 A	
		Maximum inrush current	-	6 A	
		Output residual voltage at ON	-	Standard output: 1.2 V or less High current output: 0.4 V or less	
		Leak current at OFF	-	0.1 mA or less	
		Output response time	-	0.2 ms or less (OFF to ON) 1.5 ms or less (ON to OFF)	
		Surge suppressor	-	Zener diode	
		I/O power supply voltage	-	12/24 VDC (allowable voltage from 10.2 to 28.8 VDC)	
		I/O power current consumption	-	55 mA max. (at 24 VDC)	
		Output reverse voltage protection	-	Standard output: Yes High current output: No	
		Common	-	Switchable per channel	
Power supply	Power supply voltage		24 VDC ± 15 % (SELV and LIM power supplies or Class 2 power supplies)*1		
	Current consumption		50 mA max. (at 24 VDC)		
Size			85 × 63 × 39.9 mm (W × H × D)		
Weight			Approx. 115 g (including terminal blocks, when not wired)		
Environmental resistance	Operation temperature/humidity		0 to +55 °C/5 to 95 % RH (no freezing and no condensation)		
	Storage temperature/humidity		-25 to +75 °C/5 to 95 % RH (no freezing and no condensation)		
	Vibration resistance		IEC 61131-2 compliant		
	Shock resistance		IEC 61131-2 compliant		
	Atmosphere		No corrosive gas		
	Operating altitude		0 to 2000 m		
	Installation location		In door use		
	Degree of protection		IP20		
Measurement category			II or lower		
Pollution degree			2 or lower		
Applicable regulations	CE marking	EMC	EMC Directive (2014/30/EU)		
		Environment	RoHS Directive (2011/65/EU)		
	China RoHS	Environment	Regulation 32		
Applicable standard			EN 61131-2		

*1. Use a Class 2 power supply or a power supply compliant with SELV (Safety Extra-Low Voltage) circuit and LIM (Limited Energy Circuit) circuit standards.

OPTEX FA CO., LTD.

78046-00-001-2304

page2/2