

COMPRESSION SLIDE FITTINGS IN PTFE SEALANT GLAND + STAINLESS STEEL
PRESSING BUSH FOR Ø 3 mm

Specially designed to allow the direct immersion of the entire range of
thermoelements with mineral insulation



				Y mm	X mm	HEX mm	hex mm
		1/8	NPT	10	~35	12	13
			GAS	10	~35	14	
		1/4	NPT	15	~45	17	
			GAS	10	~40	17	
		3/8	NPT	15	~45	17	
			GAS	15	~45	22	
		1/2	NPT	20	~50	22	
			GAS	15	~45	24	

TECHNICAL SPECIFICATION

Ferrule	PTFE ring + stainless steel packing
Sheath diameter d=	Ø 3 mm
For probe	Ø 3 mm
Fixing system	threaded connection
Process Connection	threaded 1/8" GAS CIL. acc. UNI-ISO 228 threaded 1/8" NPT acc. ANSI B 1.20.1 threaded 1/4" CYL. GAS acc. UNI-ISO 228 threaded 1/4" NPT acc. ANSI B 1.20.1 threaded 3/8" CYL. GAS acc. UNI-ISO 228 threaded 3/8" NPT acc. ANSI B 1.20.1 threaded 1/2" CYL. GAS acc. UNI-ISO 228 threaded 1/2" NPT acc. ANSI B 1.20.1
Sheet material	AISI 316
Type of tightness	ring PTFE PN MAX 20 BAR (T MAX 100 °C)